



Dart Aerospace Ltd.
1270 Aberdeen St
Hawkesbury, ON
K6A 1K7
Canada

Tel (613) 632-5200

D350-636-012
Job Sheet 180134



Part No: D350-636-012

Job Qty: 1 ea

Part Name: Skidtube RH, Std Wearplates, DART (Apical) Cylindrical/Aerazur Float Comp.



Part Weight: 0 lbs

Status: Scheduled

Priority: Medium

Job Created: 6/29/18

Job Tracking No:

Due Date: 7/26/18

Created By: Marie Lajeunesse

Type: Stock

Description:

Note: DWG D3492 REV E SHEET 1, D2750-042 REV G SHEETS 1,2,5,9 IPP Rev:I 02.09.25 IPP Rev:J 06-03-23 As per Rev D IPP Rev:K 06-07.13 As per dsi9343 IPP Rev:L 07-07-28 Added SS Wearplates(Rev E) JLM Verf:EC IPP Rev:M 08-04-22 DD verified:EC IPP Rev:N 08-09-23 revF DD verified:ec IPP Rev:O 09-02-06 per PAR09-010 DD verf:EC IPP Rev:P 10.06.22 revise seq110 DD verf:EC IPP Rev:Q 10.10.01 as per IIN revH DDverf:EC IPP REV:R 13.08.27 PER ECN13-594 DD VERF:JLM

Ship Via:

Bill of Materials

Job Routing

Op No	Operation	Qty	Start Date	Due Date	Standard		Workcenter/Supplier		Sign-off
					Setup hrs	Run Hrs	Workcenter / Supplier	Lead Time	
90	Start up Operation	1 Ea	7/26/18	7/26/18	0.00	0.00	Start Up Skidtubes-1		Mb/
110	Skidtubes	1 pcs	7/26/18	7/26/18	0.00	4.36	Skidtubes-4		Mb/ DAS 13
120	QC	1 pcs	7/26/18	7/26/18	0.00	0.00	QC10		38 DAS
130	QC	1 pcs	7/26/18	7/26/18	0.00	0.00	QC5		9-89 38
140	HandFinish	1 pcs	7/26/18	7/26/18	0.00	0.91	HandFinish1		D.R 18-08-15
150	QC	1 pcs	7/26/18	7/26/18	0.00	0.00	QC7-2		DE
160	Skidtubes	1 pcs	7/26/18	7/26/18	0.00	4.36	Skidtubes-1		DE
170	QC	1 pcs	7/26/18	7/26/18	0.00	0.00	QC10		D 18-08-23
180	QC	1 pcs	7/26/18	7/26/18	0.00	0.00	QC5		D 18-08-23
190	HandFinish	1 pcs	7/26/18	7/26/18	0.00	0.91	HandFinish2		
200	SprayPaint	1 pcs	7/26/18	7/26/18	0.00	0.69	Spray Paint	DAS 13	AUG 27 2018
205	Outsource	1 pcs	7/26/18	7/26/18			ATE003-VC	9-89	PO: 40856
210	QC	1 pcs	7/26/18	7/26/18	0.00	0.00	QC14		18-08-23
230	HandFinish	1 pcs	7/26/18	7/26/18	0.00	0.91	HandFinish4		18-08-23
240	QC	1 pcs	7/26/18	7/26/18	0.00	0.00	QC5		AUG 30 2018 68
250	Packaging	1 pcs	7/26/18	7/26/18	0.00	0.00	Packaging1-3		AUG 30 2018-89
260	QC	1 pcs	7/26/18	7/26/18	0.00	0.00	QC4		9-89
270	Packaging	1 pcs	7/26/18	7/26/18	0.00	0.00	Packaging3-1		DAS 69
275	DC	1 pcs	7/26/18	7/26/18	0.00	0.00	DC		21
280	QC21-FG	1 Ea	7/26/18	7/26/18	0.00	0.00	QC21		9-89

Part Op 110 - 1- Pick D2600-3 Bent Drill pilot holes as per Dwg D2750 sheet 4 (D2750-2 details). Drill using drill Jig DT8150 & Descriptions: DT8863A for second side only DT8863B for first side (detail K) 4- Locate DT8329 off of blade fitting bolt holes and drill pilot holes for blade fitting. Open to 0.500" using hole saw. VERIFY AND RECORD FWD BEND ANGLE. 6- Drill pilot holes for wearplates as per Dwg D2750 using DT8108 open to 0.297". 7- Open up holes of Detail J to 0.297" (total of 2 holes per side) 8- Weld D2744 Cap as per Dwg D2750 and QSI 004. Fill grooves in bend left from bending as per QSI 004 9- Grind welds flush as per Dwg D2750

160 - 1- Open up holes of Detail L using hole saw and ground handling to 0.625" (total of 8 holes per side) as per dwg D2750. 2- Open up holes of Detail K using hole saw to 0.750" (total of 4 holes per side) as per dwg D2750. 3- Open float holes using uni-bit to .500" (4 per Side) 4- Chamfer holes of Detail K, L, ground handling and float holes per dwg D2750 (welding instructions on sheet 9) 5- Deburr and blow out all chips from inside of tube 6- Prepare tube for welding, remove alodine as required. 7- Bond web D2739 in place as per QSI 015, let cure for 12hrs. A/R Sikaflex-291 batch: 135874 exp. date: 18/06/18 ***ATTN: USE I-BEAM LOCATION AID (BLADE FITTING)*** 8- Weld spacers D3490-1, D3490-3

DQA: _____ Date: _____

WORK ORDER NON-CONFORMANCE / UPDATE

QA Closed: _____ Date: _____

Work Order update only ☐

Work Date :	 Disposition	AGAINST DEPARTMENT/PROCESS <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 33%;"> Cross tube ☐ Small Fab ☐ Finishing ☐ Composite ☐ </td> <td style="width: 33%;"> Water Jet ☐ Prod. Eng. Coord. ☐ Rec/Store/Packaging ☐ Supplier ☐ </td> <td style="width: 33%;"> Engineering ☐ Quality ☐ Other ☐ </td> </tr> </table>	Cross tube ☐ Small Fab ☐ Finishing ☐ Composite ☐	Water Jet ☐ Prod. Eng. Coord. ☐ Rec/Store/Packaging ☐ Supplier ☐	Engineering ☐ Quality ☐ Other ☐
Cross tube ☐ Small Fab ☐ Finishing ☐ Composite ☐	Water Jet ☐ Prod. Eng. Coord. ☐ Rec/Store/Packaging ☐ Supplier ☐	Engineering ☐ Quality ☐ Other ☐			
Container No: S09981 Part: D350 - 636 - 012 Job No: 180134 Serial No/Batch: S0998 Revision: Inspector: Exp Date: Instructions: TC STC SH99 - 7		MRB (QSI042) Approval			
		Completed By			
		Lead hand / Supervisor Approval Verification			
		QC / QA Coordinator Approval			

Root Cause	FAULT CATEGORY				
<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;"> Environment ☐ Design ☐ Doc/Data ☐ Equip/Tooling ☐ Handling/Pre ☐ Material ☐ Internal Transport ☐ Tribal Knowledge ☐ LOA ☐ Substation ☐ Past Expiry Date ☐ Misidentified ☐ </td> <td style="width: 50%;"> No Re-verification ☐ Operator ☐ Offset/Setup ☐ Supplier ☐ Training ☐ Use for Testing ☐ Poor Information ☐ Rushing ☐ Product Improvement ☐ Process Improvement ☐ Manufacturing Process ☐ Past Due ☐ </td> </tr> </table>	Environment ☐ Design ☐ Doc/Data ☐ Equip/Tooling ☐ Handling/Pre ☐ Material ☐ Internal Transport ☐ Tribal Knowledge ☐ LOA ☐ Substation ☐ Past Expiry Date ☐ Misidentified ☐	No Re-verification ☐ Operator ☐ Offset/Setup ☐ Supplier ☐ Training ☐ Use for Testing ☐ Poor Information ☐ Rushing ☐ Product Improvement ☐ Process Improvement ☐ Manufacturing Process ☐ Past Due ☐	<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;"> Pressure/Forced ☐ Bending ☐ Centre Not Concentric ☐ Cracks ☐ Crimp/Kink/Ripple/Wave ☐ Cuffs ☐ Crushing ☐ Heat Treat ☐ Wave/Twist in Tube ☐ Marks/Chatter ☐ </td> <td style="width: 50%;"> Temperature/Cure ☐ Set-up ☐ BOM/Route ☐ Broken/Damage/Defect ☐ Inspection Incomplete/Unqualified ☐ Contamination ☐ Countersink ☐ Cut Too Short ☐ Instructions Incomplete/Unclear ☐ Drill Holes ☐ </td> </tr> </table>	Pressure/Forced ☐ Bending ☐ Centre Not Concentric ☐ Cracks ☐ Crimp/Kink/Ripple/Wave ☐ Cuffs ☐ Crushing ☐ Heat Treat ☐ Wave/Twist in Tube ☐ Marks/Chatter ☐	Temperature/Cure ☐ Set-up ☐ BOM/Route ☐ Broken/Damage/Defect ☐ Inspection Incomplete/Unqualified ☐ Contamination ☐ Countersink ☐ Cut Too Short ☐ Instructions Incomplete/Unclear ☐ Drill Holes ☐
Environment ☐ Design ☐ Doc/Data ☐ Equip/Tooling ☐ Handling/Pre ☐ Material ☐ Internal Transport ☐ Tribal Knowledge ☐ LOA ☐ Substation ☐ Past Expiry Date ☐ Misidentified ☐	No Re-verification ☐ Operator ☐ Offset/Setup ☐ Supplier ☐ Training ☐ Use for Testing ☐ Poor Information ☐ Rushing ☐ Product Improvement ☐ Process Improvement ☐ Manufacturing Process ☐ Past Due ☐				
Pressure/Forced ☐ Bending ☐ Centre Not Concentric ☐ Cracks ☐ Crimp/Kink/Ripple/Wave ☐ Cuffs ☐ Crushing ☐ Heat Treat ☐ Wave/Twist in Tube ☐ Marks/Chatter ☐	Temperature/Cure ☐ Set-up ☐ BOM/Route ☐ Broken/Damage/Defect ☐ Inspection Incomplete/Unqualified ☐ Contamination ☐ Countersink ☐ Cut Too Short ☐ Instructions Incomplete/Unclear ☐ Drill Holes ☐				
OTHER :					

and D2743 as per dwg D2750 & QSI004 (welding instructions on sheet 9) A/R Aluminum Rod batch: 138834 9- At section AP-AP drill out x-bolt spacer to 0.404" 10-Grind welds flush as per Dwg D2750 11- Spot face ground handling holes section (total of 4 places per side) as per dwg D2750 12- Deburr holes, ensure tube is free of all scratches before sending to paint.

180 - ***VERIFY C'BOARD IS GOOD***

190 - Re-alodine tube as per QSI 005 section 4.1.2.1 do not acid etch.

200 - 1- PRIME AS PER DWG AND QSI 005 4.2 PRIMER PRC DESOTO 515X349 BATCH: _____ 2-

PAINT WHITE AS PER DWG AND QSI 005 4.2 PAINT BATCH: _____

210 - Inspect for foreign object per QSI 024

230 - 1-Install inserts as per dwg D2750 2-Inspect for Foreign Objects 3-Install blade fitting D3488-042, wearshoes and ground handling hardware as per dwg D2750 SIKA FLEX 241 BATCH: M1138874 EXP DATE: 18/01

4-assemble o'ring to plug as per dwg D3492 and apply o'ring lube A/R 55-o'ring lube batch: 4138842 5-Coat all exposed fasteners with "LPS Procyon" batch: M1133690

270 - Package as per PPP D350-636-012

275 - record fwd angle: 89.8 Photocopy blue file and type labels per PPP D350-636-012 CHG 007

Job BOM

005232

Part / Item	Component Name	Quantity	Operation	Container
D2600-3-BENT-RH	Extrusion Bent RH	1 Ea (1 ea)	90-Start up Operation	5081485
D2744	Cap	1 Ea (1 ea)	110-Skidtubes	5060499
D2739	350 I-Beam	1 Ea (1 ea)	160-Skidtubes	5080893
D2743	Crossbolt Spacer	8 Ea (8 ea)	160-Skidtubes	5090612
D3490-1	Cross Bolt Spacer	4 Ea (4 ea)	160-Skidtubes	5082748
D3490-3	Cross Bolt Spacer	4 Ea (4 ea)	160-Skidtubes	5082950
ALS4-1032-225	Rivnut	38 Ea (38 ea)	230-HandFinish	5058139
AN3C5A	Bolt	34 Ea (34 ea)	230-HandFinish	5095214
AN3C6A	Bolt	4 Ea (4 ea)	230-HandFinish	5076000
AN6C44A	Bolt	4 Ea (4 ea)	230-HandFinish	5066333-1
AN8C35A	Bolt	1 Ea (1 ea)	230-HandFinish	M1137202
D2745	Bushing	8 Ea (8 ea)	230-HandFinish	5091818
D3488-042	Blade Fitting RH	1 Ea (1 ea)	230-HandFinish	5093460
D3492-1	Plug	8 Ea (8 ea)	230-HandFinish	5077557
D3492-3	Plug	8 Ea (8 ea)	230-HandFinish	5091848
D3535-25	Wearplate Center	1 Ea (1 ea)	230-HandFinish	5082036
D3536-25	Gasket Center	1 Ea (1 ea)	230-HandFinish	5099641
D3537-1	Wearpad	3 Ea (3 ea)	230-HandFinish	5083461
D3631-1	Washer	8 Ea (8 ea)	230-HandFinish	5058407
D3791-1	Wearpad	1 Ea (1 ea)	230-HandFinish	5081696
D3793-1	Wearplate Fwd	1 Ea (1 ea)	230-HandFinish	5089342
D3793-3	Wearplate Aft	1 Ea (1 ea)	230-HandFinish	5089448
D3794-1	Gasket Fwd	1 Ea (1 ea)	230-HandFinish	5071970
D3794-3	Gasket Aft	1 Ea (1 ea)	230-HandFinish	5081738
MS21043-6	Nut	4 Ea (4 ea)	230-HandFinish	5083547
MS21083C8	Nut	1 Ea (1 ea)	230-HandFinish	5080633
NAS1149C0332R	Washer	38 Ea (38 ea)	230-HandFinish	5071663
NAS1149C0832R	Washer	1 Ea (1 ea)	230-HandFinish	5076017
NAS1515H3L	Washer	4 Ea (4 ea)	230-HandFinish	5083559
NAS1611-010	O-Ring	8 Ea (8 ea)	230-HandFinish	5092499
NAS1611-013	O-Ring	8 Ea (8 ea)	230-HandFinish	5057659
AN8C21A	Bolt	2 Ea (2 ea)	250-Packaging	5106744
D2741	Replacement Blade	1 Ea (1 ea)	250-Packaging	5082386
D3493-1	Washer	2 Ea (2 ea)	250-Packaging	5095455
D3532-1	Spacer	2 Ea (2 ea)	250-Packaging	5090421
MS21083C8	Nut	2 Ea (2 ea)	250-Packaging	5083551
NAS1149D0863J	Washer	2 Ea (2 ea)	250-Packaging	5089247

Job Allocations

Operation	Component Part	Required	Inventory	Allocated
90-Start up Operation	D2600-3-BENT-RH	1	19	0
110-Skidtubes	D2744	1	60	0
160-Skidtubes	D2739	1	37	0
	D2743	8	87	0
	D3490-1	4	203	0
	D3490-3	4	130	0

DQA: _____ Date: _____



WORK ORDER NON-CONFORMANCE / UPDATE

QA Closed: _____ Date: _____

Work Order update only ☐

Work Order: _____ Part No. _____ NCR No. _____	DISPOSITION Rework ☐ Scrap ☐ Use-as-is ☐ Suspected Unapproved ☐	AGAINST DEPARTMENT/PROCESS Skid-tube ☐ Machining ☐ Thermoforming ☐ Large Fab ☐ Cross tube ☐ Small Fab ☐ Finishing ☐ Composite ☐ Water Jet ☐ Prod. Eng. Coord. ☐ Rec/Store/Packaging ☐ Supplier ☐ Engineering ☐ Quality ☐ Other ☐			
Date :	Step #:	QTY Effective :		MRB (QSI042) Approval	
Description Work Order Deviation		Disposition		Completed By	
				Lead hand / Supervisor Approval Verification	
				QC / QA Coordinator Approval	
Root Cause		FAULT CATEGORY			
Environment ☐	No Re-verification ☐	Pressure/Forced ☐	Temperature/Cure ☐	Power Loss/Surge ☐	Positioned Wrong ☐
Design ☐	Operator ☐	Bending ☐	Set-up ☐	Folio/Program ☐	Outside Dimensions ☐
Doc/Data ☐	Offset/Setup ☐	Centre Not Concentric ☐	BOM/Route ☐	Grain ☐	Over/Under tolerance ☐
Equip/Tooling ☐	Supplier ☐	Cracks ☐	Broken/Damage/Defect ☐	Weld ☐	Part Incorrect ☐
Handling/Pre ☐	Training ☐	Crimp/Kink/Ripple/Wave ☐	Inspection Incomplete/Unqualified ☐	Wrong Stock Pulled ☐	Part Lost/Missing ☐
Material ☐	Use for Testing ☐	Cuffs ☐	Contamination ☐	Out of Sequence ☐	Part Moved ☐
Internal Transport ☐	Poor Information ☐	Crushing ☐	Countersink ☐	Off-set ☐	Drawing ☐
Tribal Knowledge ☐	Rushing ☐	Heat Treat ☐	Cut Too Short ☐	Mislabeled ☐	Finish ☐
LOA ☐	Product Improvement ☐	Wave/Twist in Tube ☐	Instructions Incomplete/Unclear ☐	Fit/Function ☐	Misread ☐
Substation ☐	Process Improvement ☐	Marks/Chatter ☐	Drill Holes ☐	Misaligned/off center ☐	Turning Sequence ☐
Past Expiry Date ☐	Manufacturing Process ☐	OTHER :			
Misidentified ☐	Past Due ☐				

230-HandFinish

ALS4-1032-225	38	4,225	0
AN3C5A	34	2,030	0
AN3C6A	4	392	0
AN6C44A	4	283	0
AN8C35A	1	46	0
D2745	8	85	0
D3488-042	1	6	0
D3492-1	8	248	0
D3492-3	8	79	0
D3535-25	1	43	0
D3536-25	1	41	0
D3537-1	3	209	0
D3631-1	8	803	0
D3791-1	1	37	0
D3793-1	1	11	0
D3793-3	1	11	0
D3794-1	1	37	0
D3794-3	1	43	0
MS21043-6	4	240	0
MS21083C8	1	133	0
NAS1149C0332R	38	5,107	0
NAS1149C0832R	1	438	0
NAS1515H3L	4	635	0
NAS1611-010	8	429	0
NAS1611-013	8	1,325	0
AN8C21A	2	106	0
D2741	1	115	0
D3493-1	2	27	0
D3532-1	2	10	0
MS21083C8	2	133	0
NAS1149D0863J	2	77	0

250-Packaging

Part Specifications

Specifications could not be found.

DQA: _____ Date: _____



WORK ORDER NON-CONFORMANCE / UPDATE

QA Closed: _____ Date: _____

Work Order update only ☐

Work Order: _____ Part No. _____ NCR No. _____		DISPOSITION Rework ☐ Scrap ☐ Use-as-is ☐ Suspected Unapproved ☐		AGAINST DEPARTMENT/PROCESS Skid-tube ☐ Machining ☐ Thermoforming ☐ Large Fab ☐ Cross tube ☐ Small Fab ☐ Finishing ☐ Composite ☐ Water Jet ☐ Prod. Eng. Coord. ☐ Rec/Store/Packaging ☐ Supplier ☐ Engineering ☐ Quality ☐ Other ☐					
Date :		Step #:		QTY Effective :			MRB (QSI042) Approval		
Description Work Order Deviation				Disposition				Completed By	
								Lead hand / Supervisor Approval Verification	
								QC / QA Coordinator Approval	
Root Cause		FAULT CATEGORY							
Environment ☐	No Re-verification ☐	Pressure/Forced ☐	Temperature/Cure ☐	Power Loss/Surge ☐	Positioned Wrong ☐				
Design ☐	Operator ☐	Bending ☐	Set-up ☐	Folio/Program ☐	Outside Dimensions ☐				
Doc/Data ☐	Offset/Setup ☐	Centre Not Concentric ☐	BOM/Route ☐	Grain ☐	Over/Under tolerance ☐				
Equip/Tooling ☐	Supplier ☐	Cracks ☐	Broken/Damage/Defect ☐	Weld ☐	Part Incorrect ☐				
Handling/Pre ☐	Training ☐	Crimp/Kink/Ripple/Wave ☐	Inspection Incomplete/Unqualified ☐	Wrong Stock Pulled ☐	Part Lost/Missing ☐				
Material ☐	Use for Testing ☐	Cuffs ☐	Contamination ☐	Out of Sequence ☐	Part Moved ☐				
Internal Transport ☐	Poor Information ☐	Crushing ☐	Countersink ☐	Off-set ☐	Drawing ☐				
Tribal Knowledge ☐	Rushing ☐	Heat Treat ☐	Cut Too Short ☐	Mislabeled ☐	Finish ☐				
LOA ☐	Product Improvement ☐	Wave/Twist in Tube ☐	Instructions Incomplete/Unclear ☐	Fit/Function ☐	Misread ☐				
Substation ☐	Process Improvement ☐	Marks/Chatter ☐	Drill Holes ☐	Misaligned/off center ☐	Turning Sequence ☐				
Past Expiry Date ☐	Manufacturing Process ☐	OTHER :							
Misidentified ☐	Past Due ☐								

QTY -041	QTY -042	QTY -043	QTY -044	PART NUMBER	DESCRIPTION
X				D2750-041	350 SKIDTUBE ASSEMBLY, LH
	X			D2750-042	350 SKIDTUBE ASSEMBLY, RH
		X		D2750-043	350 SKIDTUBE ASSEMBLY, LH
			X	D2750-044	350 SKIDTUBE ASSEMBLY, RH
1	1	1	1	D2739	WEB
8	8	8	8	D2743	SPACER
1	1	1	1	D2744	CAP
8	8	8	8	D2745	BUSHING
1				D2750-1	SKIDTUBE WELDMENT, LH
	1			D2750-2	SKIDTUBE WELDMENT, RH
		1		D2750-3	SKIDTUBE WELDMENT, LH
			1	D2750-4	SKIDTUBE WELDMENT, RH
1		1		D3488-041	BLADE FITTING, LH
	1		1	D3488-042	BLADE FITTING, RH
4	4	4	4	D3490-1	SPACER
4	4			D3490-3	SPACER
		4	4	D3490-5	SPACER
8	8	8	8	D3492-041	PLUG ASSEMBLY
8	8			D3492-043	PLUG ASSEMBLY
		8	8	D3492-045	PLUG ASSEMBLY
1	1	1	1	D3535-25	WEARSHOE
1	1	1	1	D3536-25	GASKET
3	3	3	3	D3537-1	WEARPAD
8	8	8	8	D3631-1	WASHER
1	1	1	1	D3791-1	WEARPLATE
1	1	1	1	D3793-1	WEARSHOE
1	1	1	1	D3793-3	WEARSHOE
1	1	1	1	D3794-1	GASKET
1	1	1	1	D3794-3	GASKET
38	38	38	38	ALS4-1032-225	INSERT (OR ALS7-1032-225, AKS4-1032-225, AELS-1032-225)
34	34	34	34	AN3C5A	BOLT
4	4	4	4	AN3C6A	BOLT
4	4	4	4	AN6C44A	BOLT
1	1	1	1	AN8C35A	BOLT
38	38	38	38	AN960C10L	WASHER
1	1	1	1	AN960C816L	WASHER
4	4	4	4	MS21043-6	NUT
1	1	1	1	MS21083C8	NUT
4	4	4	4	NAS1515H3L	WASHER

GENERAL NOTES:

- MATERIAL: MAKE D2750-1/-2/-3/-4 FROM D2600-3 EXTRUSION (INITIAL LENGTH = 120.0).
- FINISH: ACID ETCH, ALODINE ASSEMBLY PER DART QSI 005 4.1 PRIOR TO INSTALLING D2739 WEB.
STANDARD: PRIME (REF. 4.2.1.3.3) AND PAINT WHITE PER DART QSI 005 4.2
OPTIONAL: POWDER COAT WHITE (REF. 4.3.5.1) PER DART QSI 005 4.3
BLACK ANTI-SKID PAINT AS INDICATED TO 1.0 ABOVE SKIDTUBE CENTER-LINE PER DART 005 4.4 (OPTIONAL).
- TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- UNITS: INCHES UNLESS OTHERWISE NOTED
- BREAK SHARP EDGES: N/A
- IDENTIFICATION: N/A
- WEIGHT: D2750-041/-042/-043/-044 = 26.5 LBS
- WELD PER DART QSI 004
- INSTALL ALS4-1032-225 INSERTS AFTER FINISH AS INDICATED. DRILL 'F' SIZE HOLES ($\phi 0.297$) FOR WEARSHOE INSERTS
- FINAL CONFIGURATION SHOULD HAVE THE FOLLOWING MINIMUM MECHANICAL PROPERTIES:
MINIMUM YIELD TENSILE STRENGTH = 35 KSI
MINIMUM ULTIMATE TENSILE STRENGTH = 38 KSI
- COAT ALL EXPOSED FASTENERS WITH LPS LABORATORIES "LPS PROCYON" AFTER FINAL ASSEMBLY, CLEAN EXCESS OFF
FINISH WITH MEK DEGREASER.
- SPACER AND PLUG INSTALLED SAME AS SECTION AJ-AJ EXCEPT HORIZONTAL
- SPACER AND PLUG INSTALLED SAME AS SECTION AP-AP EXCEPT HORIZONTAL

SHOP COPY
RETURN TO
ENGINEERING
UNCONTROLLED COPY
SUBJECT TO AMENDMENT
WITHOUT NOTICE
WORK ORDER

NO. 180134 MJS
1806-29

RELEASED
2013-08-13
WD

G	CORRECTED TOLERANCE ON $\phi 0.500$ THRU HOLE: IS +0.010/-0.000, WAS +0.100/-0.000 (ZN B3-4, B2-5); ADD VIEW TO CONTROL FWD BEND ORIENTATION (ZN D-1-4/-5/-6/-7); UPDATED FINISH OPTIONS; INSIDE OF TUBE NO LONGER SPRAYED WITH LPS-3. REASON: PAR13-276 AND NCR13-2757	MB	13.07.11
F	INCORPORATE DSI 9413; QTY (3) D3537-1 WAS QTY (5) (ZN C8-1); D3791-1/-3 REPLACES D3535-13/-35 (ZN C8-1); D3794-1/-3 REPLACES D3536-13/-35 (ZN B8-1); ADD D3791-1 (ZN C8-1); WEARSHOE HOLES UNDER FWD/AFT SADDLE REMOVED (8 PL). WEARSHOE HARDWARE QTY UPDATED (ZN B8-1); D3488-041/-042 HARDWARE UPDATED (ZN C1-8, 9, 10, 11); ADD NOTE 12 AND 13 (ZN A6-1); REASON: REF. NCR 08-043	PH	08.07.16
E	CHANGE TO STAINLESS STEEL WEARPLATES; ADD RUBBER GASKETS; CHANGE INSERTS; ADD D3631-1; REMOVE QTY (38) NAS1515H3L; REMOVE QTY (10) NAS1515H8L; REMOVE D2741; QTY (2) AN960C816; REMOVE QTY (2) MS21083C8	CB	07.05.17
D	ADD HOLES AND SPACERS FOR APICAL FLOATS; INCORPORATE DED 9133/9157	PH	06.01.05
C	ADD D2750-3/D2750-4; INCORPORATE D2738 AND D2740	CP	98.11.18
B	CHANGE MS24694-S293 TO AN8-16A	CP	98.09.01
A	NEW ISSUE	DS	98.04.16
REV.	DESCRIPTION	BY	DATE
DESIGN	MM		
DRAWN			
CHECKED			
MFG. APPR.			
APPROVED			
DE APPR.			
DATE	13.07.11		

DART AEROSPACE USA, INC.


KENT, WA

DRAWING NO.
D2750

TITLE
350 SKIDTUBE ASSEMBLY

REV. G
SHEET 1 OF 11
SCALE
NTS

COPYRIGHT © 1998 BY DART AEROSPACE USA, INC.
THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS
NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT
WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.





D2750-041 350 SKIDTUBE ASSEMBLY, LH

D2750-042 350 SKIDTUBE ASSEMBLY, RH

RELEASED
2013-08-13
ND


DESIGN	MM	DART AEROSPACE USA, INC.	
DRAWN		KENT, WA	
CHECKED		DRAWING NO. D2750	REV. G
MFG. APPR.		TITLE	SHEET 2 OF 11
APPROVED		350 SKIDTUBE ASSEMBLY	SCALE
DE APPR.			NTS
DATE	13.07.11	COPYRIGHT © 1989 BY DART AEROSPACE USA, INC. THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL, AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.	

8 7 6 5 4 3 2 1




MAX ALLOWABLE
TWIST ON FWD BEND
(VIEWED LOOKING FWD)


D2750-2 RH SKIDTUBE




DETAIL J
SCALE 2X




DETAIL K
SCALE 2X




DETAIL L
SCALE 2X




DETAIL M
SCALE 2X




SECTION N-N
SCALE 3X, 2 PL



SECTION P-P
SCALE 3X, 17 PL



SECTION Q-Q
SCALE 3X, 4 PL



SECTION R-R
SCALE 3X, 4 PL

RELEASED
2013-08-13

DESIGN	MM	DART AEROSPACE USA, INC.	
DRAWN		KENT, WA	
CHECKED		DRAWING NO.	REV. G
MFG. APPR.		D2750	SHEET 5 OF 11
APPROVED		TITLE	SCALE
DE APPR.		350 SKIDTUBE ASSEMBLY	NTS
DATE	13.07.11	COPYRIGHT © 1990 BY DART AEROSPACE USA, INC.	
		THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL, AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE REPRODUCED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.	

8 7 6 5 4 3 2 1



DART AEROSPACE USA, INC.

IIN-D350-636

Page 24 of 31

5.0 PARTS LIST

(D350-636-011/-012/-013/-014 SKIDTUBES AT CHANGE 003)

Item	Qty -011	Qty -012	Qty -013	Qty -014	Qty -043	Part Number	Description
	X					D350-636-011	SKIDTUBE INSTALLATION, LH, STD AERAZUR/APICAL CYLINDRICAL FLOAT COMPATIBLE
		X				D350-636-012	SKIDTUBE INSTALLATION, RH, STD AERAZUR/APICAL CYLINDRICAL FLOAT COMPATIBLE
			X			D350-636-013	SKIDTUBE INSTALLATION, LH AIRCRAUSER/ APICAL TRI-BAG FLOAT COMPATIBLE
				X		D350-636-014	SKIDTUBE INSTALLATION, RH AIRCRAUSER/ APICAL TRI-BAG FLOAT COMPATIBLE
					X	D350-636-043	WEARSHOE KIT (REPLACES -041 KIT)
1	1					D2750-041	SKIDTUBE ASSEMBLY, LH
1		1				D2750-042	SKIDTUBE ASSEMBLY, RH
1			1			D2750-043	SKIDTUBE ASSEMBLY, LH
1				1		D2750-044	SKIDTUBE ASSEMBLY, RH
*1	1					D2750-1	SKIDTUBE WELDMENT, LH
*1		1				D2750-2	SKIDTUBE WELDMENT, RH
*1			1			D2750-3	SKIDTUBE WELDMENT, LH
*1				1		D2750-4	SKIDTUBE WELDMENT, RH
**2	8	8	8	8		350A41-1027-20	SCREW
**3	8	8	8	8		23119AG120LE	WASHER
**4	8	8	8	8		22541N120	NUT
*5	1	1	1	1		AN8C35A	BOLT (REPLACES AN8-35A)
*6A	2	2	2	2		AN960C816L	WASHER (REPLACES AN960JD816)
*6B	2	2	2	2		NAS1515H8L	WASHER
*7	1	1	1	1		MS21083C8	NUT (REPLACES MS21083N8)
*8	1		1			D3488-041	BLADE FITTING, LH (REPLACES D2742-1)
*8		1		1		D3488-042	BLADE FITTING, RH (REPLACES D2742-2)
9	1	1	1	1		D2741	BLADE
10	2	2	2	2		AN8C21A	BOLT (REPLACES AN8-16A)
11A	2	2	2	2		AN960C816L	WASHER (REPLACES AN960JD816)
11B	2	2	2	2		D3672-13	WASHER
12	2	2	2	2		MS21083C8	NUT (REPLACES MS21083N8)
*13	4	4	4	4		ALS4-1032-225	INSERT
*14	4	4	4	4		AN6C44A	BOLT (REPLACES AN6-44A)
*15	8	8	8	8		D2745	BUSHING
*16	4	4	4	4		MS21043-6	NUT (REPLACES MS21042L6)
*17	8	8	8	8		D3631-1	WASHER (REPLACES NAS1515H8L)
*18	4	4	4	4		ALS4-1032-225	INSERT (REPLACES NAS1330S3KB166)
*19	4	4	4	4		AN3C6A	BOLT (REPLACES AN3-6A)

(CONTINUED ON NEXT PAGE)

REFERENCE ONLY

REFERENCE ONLY

REFERENCE ONLY

(CONTINUED FROM PREVIOUS PAGE)

Item	Qty -011	Qty -012	Qty -013	Qty -014	Qty -043	Part Number	Description
*20A	4	4	4	4		AN960C10L	WASHER (REPLACES AN960JD10)
*20B	4	4	4	4		NAS1515H3L	WASHER (REPLACES AN960JD10)
*22	5	5	5	5	5	D3537-1	WEARPAD (REPLACES D2648-3)
*23A	1	1	1	1	1	D3535-13	WEARSHOE (REPLACES D2656-13)
*23B	1	1	1	1	1	D3536-13	GASKET
*24A	1	1	1	1	1	D3535-25	WEARSHOE (REPLACES D2746)
*24B	1	1	1	1	1	D3536-25	GASKET
*25A	1	1	1	1	1	D3535-35	WEARSHOE (REPLACES D2656-35)
*25B	1	1	1	1	1	D3536-35	GASKET
*26A	38	38	38	38	38	AN3C5A	BOLT (REPLACES AN3-5A)
*26B	4	4	4	4	4	AN3C7A	BOLT (REPLACES AN3-7A)
*27	42	42	42	42	42	AN960C10L	WASHER (REPLACES AN960JD10)
*28	38	38	38	38		ALS4-1032-225	INSERT (REPLACES NAS1330S3KB166)
*30	8	8	8	8		D3492-041	PLUG ASSEMBLY
*31	8	8				D3492-043	PLUG ASSEMBLY
*32			8	8		D3492-045	PLUG ASSEMBLY
***43	2	2	2	2		D3493-1	WASHER
50	2	2				D3532-1	SPACER

* PART OF D2750-041/-042 OR D2750-043/-044 ASSEMBLY

** TO BE SUPPLIED BY CUSTOMER

*** ONLY INSTALLED IF INSTALLING AN APICAL FLOAT SYSTEM

REFERENCE ONLY

© COPYRIGHT © 2010 BY DART AEROSPACE USA, INC. •

THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.

Revision: J

Date: 13.03.01

REFERENCE ONLY

REFERENCE ONLY